

# Ethanol Cooking Gel

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).  
Date of Issue: 04/22/2022 Version: 1.0

### SECTION 1: IDENTIFICATION

#### 1.1. Product Identifier

**Product Form:** Mixture

**Product Name:** Ethanol Cooking Gel

**Product Code:** 17900-F925

**Synonyms:** F925

#### 1.2. Intended Use of the Product

Cooking gel.

#### 1.3. Name, Address, and Telephone of the Responsible Party

FancyHeat Corporation

40 Veronica Ave

Somerset, NJ 08873

United States

T (973)-589-1450

[customerservice@fancyheat.com](mailto:customerservice@fancyheat.com) - [www.fancyheat.com](http://www.fancyheat.com)

#### 1.4. Emergency Telephone Number

**Emergency Number** : For Chemical Emergency Call CHEMTREC day or night

Within USA and Canada: 1.800.424.9300

Mexico: 1.800.681.9531

Outside USA and Canada: 1.703.527.3887 (collect calls accepted)

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the Substance or Mixture

##### GHS-US/CA Classification

Flam. Liq. 3 H226

Eye Irrit. 2 H319

Full text of hazard classes and H-statements : see section 16

#### 2.2. Label Elements

##### GHS-US/CA Labeling

**Hazard Pictograms (GHS-US/CA)** :



**Signal Word (GHS-US/CA)** : Warning

**Hazard Statements (GHS-US/CA)** : H226 - Flammable liquid and vapor.  
H319 - Causes serious eye irritation.

**Precautionary Statements (GHS-US/CA)** : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground/bond container and receiving equipment.  
P241 - Use explosion-proof electrical, ventilating, and lighting equipment.  
P242 - Use only non-sparking tools.  
P243 - Take action to prevent static discharges.  
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.  
P280 - Wear protective gloves, protective clothing, and eye protection.  
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P370+P378 - In case of fire: Use appropriate media (see section 5) to extinguish.

# Ethanol Cooking Gel

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

P403+P235 - Store in a well-ventilated place. Keep cool.

P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

### 2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

### 2.4. Unknown Acute Toxicity (GHS-US/CA)

No additional information available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Synonyms	Product Identifier	% *	GHS Ingredient Classification
Ethyl alcohol	Methylcarbinol / Ethanol / Alcohol anhydrous / Alcohol / Grain alcohol	(CAS-No.) 64-17-5	60 - 80	Flam. Liq. 2, H225 Eye Irrit. 2A, H319
Acetone	Dimethyl ketone / 2-Propanone / Propan-2-one / Propanone	(CAS-No.) 67-64-1	1 - 5	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336

Full text of H-statements: see section 16

\*Percentages are listed in weight by weight percentage (w/w%). The actual concentration of ingredient(s) is withheld as a trade secret in accordance with the Hazardous Products Regulations (HPR) SOR/2015-17 and 29 CFR 1910.1200.

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of First-aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

**Skin Contact:** Immediately drench affected area with water for at least 15 minutes. Immediately remove contaminated clothing. Obtain medical attention if irritation develops or persists.

**Eye Contact:** Immediately rinse with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

**Ingestion:** Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

### 4.2. Most Important Symptoms and Effects Both Acute and Delayed

**General:** Causes serious eye irritation.

**Inhalation:** Prolonged exposure may cause irritation.

**Skin Contact:** Prolonged exposure may cause skin irritation.

**Eye Contact:** Contact causes severe irritation with redness and swelling of the conjunctiva.

**Ingestion:** Ingestion may cause adverse effects.

**Chronic Symptoms:** None expected under normal conditions of use.

### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

## SECTION 5: FIRE-FIGHTING MEASURES

### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO<sub>2</sub>). Water may be ineffective but water should be used to keep fire-exposed container cool.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. A heavy water stream may spread burning liquid.

### 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Flammable liquid and vapor. Alcohols burn with a pale blue flame that is difficult to see under normal lighting conditions.

**Explosion Hazard:** May form flammable or explosive vapor-air mixture. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors. An uncontrolled polymerization may produce a rapid release of energy with the potential for an explosion of unvented closed containers. May form flammable or explosive vapor-air mixture.

**Reactivity:** Reacts violently with strong oxidizers. Increased risk of fire or explosion.

# Ethanol Cooking Gel

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

### 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Carbon oxides (CO, CO<sub>2</sub>). Nitrogen oxides.

### 5.4. Reference to Other Sections

Refer to Section 9 for flammability properties.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Avoid breathing (vapor, mist, spray). Do not get in eyes, on skin, or on clothing. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use special care to avoid static electric charges.

#### 6.1.1. For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protective equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel. Stop leak if safe to do so.

#### 6.1.2. For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Eliminate ignition sources first, then ventilate the area.

### 6.2. Environmental Precautions

Prevent entry to sewers and public waters.

### 6.3. Methods and Materials for Containment and Cleaning Up

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Use only non-sparking tools. Absorb and/or contain spill with inert material. Do not take up in combustible material such as: saw dust or cellulosic material. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

### 6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for Safe Handling

**Additional Hazards When Processed:** Handle empty containers with care because residual vapors are flammable.

**Precautions for Safe Handling:** Avoid contact with skin, eyes and clothing. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid breathing vapors, mist, spray. Take precautionary measures against static discharge. Use only non-sparking tools.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures.

### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations. Take action to prevent static discharges. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment.

**Storage Conditions:** Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store in a well-ventilated place. Keep container tightly closed. Keep in fireproof place.

**Incompatible Materials:** Oxidizing agent. Reducing agents. Alkali metals. Aldehydes. Amines.

### 7.3. Specific End Use(s)

Cooking gel.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

Ethyl alcohol (64-17-5)		
USA ACGIH	ACGIH OEL STEL	1000 ppm

# Ethanol Cooking Gel

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

<b>USA ACGIH</b>	ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
<b>USA OSHA</b>	OSHA PEL TWA	1900 mg/m <sup>3</sup>
<b>USA OSHA</b>	OSHA PEL TWA	1000 ppm
<b>USA NIOSH</b>	NIOSH REL (TWA)	1900 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL TWA	1000 ppm
<b>USA IDLH</b>	IDLH	3300 ppm (10% LEL)
<b>Alberta</b>	OEL TWA	1880 mg/m <sup>3</sup>
<b>Alberta</b>	OEL TWA	1000 ppm
<b>British Columbia</b>	OEL STEL	1000 ppm
<b>Manitoba</b>	OEL STEL	1000 ppm
<b>New Brunswick</b>	OEL TWA	1880 mg/m <sup>3</sup>
<b>New Brunswick</b>	OEL TWA	1000 ppm
<b>Newfoundland &amp; Labrador</b>	OEL STEL	1000 ppm
<b>Nova Scotia</b>	OEL STEL	1000 ppm
<b>Nunavut</b>	OEL STEL	1250 ppm
<b>Nunavut</b>	OEL TWA	1000 ppm
<b>Northwest Territories</b>	OEL STEL	1250 ppm
<b>Northwest Territories</b>	OEL TWA	1000 ppm
<b>Ontario</b>	OEL STEL	1000 ppm
<b>Prince Edward Island</b>	OEL STEL	1000 ppm
<b>Québec</b>	VECD OEL STEL	1000 ppm
<b>Saskatchewan</b>	OEL STEL	1250 ppm
<b>Saskatchewan</b>	OEL TWA	1000 ppm
<b>Yukon</b>	OEL STEL	1900 mg/m <sup>3</sup>
<b>Yukon</b>	OEL STEL	1000 ppm
<b>Yukon</b>	OEL TWA	1900 mg/m <sup>3</sup>
<b>Yukon</b>	OEL TWA	1000 ppm
<b>Acetone (67-64-1)</b>		
<b>USA ACGIH</b>	ACGIH OEL TWA	250 ppm
<b>USA ACGIH</b>	ACGIH OEL STEL	500 ppm
<b>USA ACGIH</b>	ACGIH chemical category	Not Classifiable as a Human Carcinogen
<b>USA ACGIH</b>	BEI BLV	25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift (nonspecific)
<b>USA OSHA</b>	OSHA PEL TWA	2400 mg/m <sup>3</sup>
<b>USA OSHA</b>	OSHA PEL TWA	1000 ppm
<b>USA NIOSH</b>	NIOSH REL TWA	590 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL TWA	250 ppm
<b>USA IDLH</b>	IDLH	2500 ppm (10% LEL)
<b>Alberta</b>	OEL STEL	1800 mg/m <sup>3</sup>
<b>Alberta</b>	OEL STEL	750 ppm
<b>Alberta</b>	OEL TWA	1200 mg/m <sup>3</sup>
<b>Alberta</b>	OEL TWA	500 ppm
<b>British Columbia</b>	OEL STEL	500 ppm
<b>British Columbia</b>	OEL TWA	250 ppm
<b>Manitoba</b>	OEL STEL	500 ppm
<b>Manitoba</b>	OEL TWA	250 ppm
<b>New Brunswick</b>	OEL STEL	1782 mg/m <sup>3</sup>
<b>New Brunswick</b>	OEL STEL	750 ppm
<b>New Brunswick</b>	OEL TWA	1188 mg/m <sup>3</sup>
<b>New Brunswick</b>	OEL TWA	500 ppm
<b>Newfoundland &amp; Labrador</b>	OEL STEL	500 ppm
<b>Newfoundland &amp; Labrador</b>	OEL TWA	250 ppm

# Ethanol Cooking Gel

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Nova Scotia	OEL STEL	500 ppm
Nova Scotia	OEL TWA	250 ppm
Nunavut	OEL STEL	750 ppm
Nunavut	OEL TWA	500 ppm
Northwest Territories	OEL STEL	750 ppm
Northwest Territories	OEL TWA	500 ppm
Ontario	OEL STEL	500 ppm
Ontario	OEL TWA	250 ppm
Prince Edward Island	OEL STEL	500 ppm
Prince Edward Island	OEL TWA	250 ppm
Québec	VECD OEL STEL	2380 mg/m <sup>3</sup>
Québec	VECD OEL STEL	1000 ppm
Québec	VEMP OEL TWA	1190 mg/m <sup>3</sup>
Québec	VEMP OEL TWA	500 ppm
Saskatchewan	OEL STEL	750 ppm
Saskatchewan	OEL TWA	500 ppm
Yukon	OEL STEL	3000 mg/m <sup>3</sup>
Yukon	OEL STEL	1250 ppm
Yukon	OEL TWA	2400 mg/m <sup>3</sup>
Yukon	OEL TWA	1000 ppm

## 8.2. Exposure Controls

**Appropriate Engineering Controls:** Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases or vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment.

**Personal Protective Equipment:** Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics. Wear fire/flammable resistant/retardant clothing.

**Hand Protection:** Wear protective gloves.

**Eye and Face Protection:** Chemical safety goggles.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

**Other Information:** When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Red gel liquid
Odor	: Mild alcohol
Odor Threshold	: No data available
pH	: No data available
Evaporation Rate	: No data available
Melting Point	: No data available
Freezing Point	: No data available
Boiling Point	: > 35 °C (95 °F)
Flash Point	: 25.6 °C (78 °F) (closed cup)
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available

# Ethanol Cooking Gel

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Flammability (solid, gas)	: Not applicable
Lower Flammable Limit	: No data available
Upper Flammable Limit	: No data available
Vapor Pressure	: No data available
Relative Vapor Density at 20°C	: No data available
Relative Density	: No data available
Specific Gravity	: No data available
Solubility	: Water: Complete
Partition Coefficient: N-Octanol/Water	: No data available
Viscosity	: No data available

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity:

Reacts violently with strong oxidizers. Increased risk of fire or explosion.

### 10.2. Chemical Stability:

Flammable liquid and vapor. May form flammable or explosive vapor-air mixture.

### 10.3. Possibility of Hazardous Reactions:

Hazardous polymerization will not occur.

### 10.4. Conditions to Avoid:

Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.

### 10.5. Incompatible Materials:

Oxidizing agent. Reducing agents. Alkali metals. Aldehydes. Amines.

### 10.6. Hazardous Decomposition Products:

Not expected to decompose under ambient conditions.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on Toxicological Effects - Product

Acute Toxicity (Oral): Not classified

Acute Toxicity (Dermal): Not classified

Acute Toxicity (Inhalation): Not classified

LD50 and LC50 Data: No additional information available

Skin Corrosion/Irritation: Not classified

Eye Damage/Irritation: Causes serious eye irritation.

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Prolonged exposure may cause irritation.

Symptoms/Injuries After Skin Contact: Prolonged exposure may cause skin irritation.

Symptoms/Injuries After Eye Contact: Contact causes severe irritation with redness and swelling of the conjunctiva.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

### 11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Ethyl alcohol (64-17-5)	
LD50 Oral Rat	10470 mg/kg
LD50 Dermal Rat	20 ml/kg
LC50 Inhalation Rat	124.7 mg/l/4h
Acetone (67-64-1)	
LD50 Oral Rat	5800 mg/kg (Species: Sprague-Dawley)
LD50 Dermal Rabbit	7400 mg/kg

# Ethanol Cooking Gel

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

LC50 Inhalation Rat	44 g/m <sup>3</sup>
---------------------	---------------------

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

Ecology - General: Not classified.

Ethyl alcohol (64-17-5)	
LC50 Fish 1	11200 mg/l
EC50 Crustacea	9268 – 14221 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 Fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
ErC50 Algae	1000 mg/l
NOEC Chronic Crustacea	9.6 mg/l

Acetone (67-64-1)	
LC50 Fish 1	4144 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Crustacea 1	1680 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 Fish 2	6210 – 8120 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Crustacea 2	12600 – 12700 mg/l (Exposure time: 48 h - Species: Daphnia magna)

### 12.2. Persistence and Degradability

Ethanol Cooking Gel	
Persistence and Degradability	Not established.
Acetone (67-64-1)	
Persistence and Degradability	Readily biodegradable in water.

### 12.3. Bioaccumulative Potential

Ethanol Cooking Gel	
Bioaccumulative Potential	Not established.
Ethyl alcohol (64-17-5)	
Partition coefficient n-octanol/water (Log Pow)	-0.32
Acetone (67-64-1)	
BCF Fish	0.69
Partition coefficient n-octanol/water (Log Pow)	-0.24

### 12.4. Mobility in Soil

No additional information available

### 12.5. Other Adverse Effects

Other Information: Avoid unnecessary release into the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

**Waste Disposal Recommendations:** Dispose of contents/container in accordance with local, regional, national, and international regulations

**Additional Information:** Handle empty containers with care because residual vapors are flammable.

**Ecology - Waste Materials:** Avoid unnecessary release into environment.

## SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

### 14.1. In Accordance with DOT

Proper Shipping Name	: ETHYL ALCOHOL SOLUTIONS
Hazard Class	: 3
Identification Number	: UN1170
Label Codes	: 3
Packing Group	: III
ERG Number	: 127
Additional Information	: Limited Quantity for packages not exceeding 30 kg gross and inner packaging not exceeding 5 L each.



# Ethanol Cooking Gel

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

### 14.2. In Accordance with IMDG

**Proper Shipping Name** : ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)  
**Hazard Class** : 3  
**Identification Number** : UN1170  
**Label Codes** : 3  
**Packing Group** : III  
**EmS-No. (Fire)** : F-E  
**EmS-No. (Spillage)** : S-D  
**Additional Information** : Limited Quantity for packages not exceeding 30 kg gross and inner packaging not exceeding 5 L each.



### 14.3. In Accordance with IATA

**Proper Shipping Name** : ETHYL ALCOHOL SOLUTION  
**Hazard Class** : 3  
**Identification Number** : UN1170  
**Label Codes** : 3  
**Packing Group** : III  
**ERG Code (IATA)** : 3L  
**Additional Information** : Limited Quantity for packages not exceeding 30 kg gross, inner packaging not exceeding 2.5 L net quantity each (glass) or 5 L net quantity each (metal/plastic), and 10 L total net quantity per package.



### 14.4. In Accordance with TDG

**Proper Shipping Name** : ETHYL ALCOHOL SOLUTION  
**Hazard Class** : 3  
**Identification Number** : UN1170  
**Label Codes** : 3  
**Packing Group** : III  
**Additional Information** : Limited Quantity for packages not exceeding 30 kg gross and inner packaging not exceeding 5 L each.



## SECTION 15: REGULATORY INFORMATION

### 15.1. US Federal Regulations

<b>Ethanol Cooking Gel</b>	
<b>SARA Section 311/312 Hazard Classes</b>	Health hazard - Serious eye damage or eye irritation Physical hazard - Flammable (gases, aerosols, liquids, or solids)
<b>Ethyl alcohol (64-17-5)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
<b>Acetone (67-64-1)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
<b>CERCLA RQ</b>	5000 lb

### 15.2. US State Regulations

<b>Ethyl alcohol (64-17-5)</b>
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List
<b>Acetone (67-64-1)</b>
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List



# Ethanol Cooking Gel

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

### 15.3. Canadian Regulations

#### Ethyl alcohol (64-17-5)

Listed on the Canadian DSL (Domestic Substances List)

#### Acetone (67-64-1)

Listed on the Canadian DSL (Domestic Substances List)

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Date of Preparation or Latest Revision** : 04/22/2022

**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17.

### GHS Full Text Phrases:

Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

NA GHS SDS 2015 (Can, US)